

## VISTA™-II Rackmount Computer



### General Description

This is an industrial grade 19 inch rack mount computer that uses industry standard PC/ATX compatible motherboards and I/O cards. The chassis has the following features:

- 19 inch rack mount, 7.00 inch height (4U) with heavy duty full extension slide out rails
- 5 to 7 slot (PCI slots and one AGP slot) ATX Form Factor motherboard
- Space for two 5¼ inch half height disk drives
- Space for one 3½ inch half height disk drive
- Internal shock mounting of one or two 3½ inch or 5¼ inch hard disk drives
- Rear access for I/O card connections
- Cut outs for DB-9, DB-25, USB and PS/2 connectors
- 250-400 Watt power supplies with internal fan
- Up to two large cooling fans in the chassis
- Front removable filter assembly for cooling air intakes
- Hard Disk Drive Access and Power LED indicators
- Power and Computer Reset switches
- Miniature audio transducer speaker
- Isolating transformer for remote amplified speaker
- Optional keyboard lock switch

### Typical Configuration

- **System:** PCI/AGP system in Industrial rackmount enclosure.
- **Processor:** Celeron®, Pentium®III or Pentium®4.
- **Memory:** 256 MB dual channel DDR400 RAM expandable to 4 GB.
- **Optional Memory:** Up to 512 kB battery backed up CMOS RAM.
- **Hard Disk:** 80 GB or larger 7200 rpm, 2 MB cache.
- **Floppy Disk:** 3.5 inch 1.44 MB floppy.
- **Optical Disk:** CD-ROM, CD-RW and DVD options available.
- **Serial I/O:** Intelligent 8 to 224 channel serial interface module for RS-232 or RS-485 with baud rates up to 115200.
- **Parallel Port:** For local printer.
- **Modem:** Dial-up or private line with baud rates up to 33600
- **Ethernet:** TCP/IP supported. Single or Dual Ethernet interface used for interprocessor link and communication with other computers. Optional TCP/IP and NFS support on V2TERM workstations.
- **Serial Multifunction Card (SMC):** Custom PCI card with hardware watchdog, battery backed up RAM.



## General Specifications

### Mechanical

- 4U22ATX400 ATX Rack-Mount Case
- 4U rackmount chassis
- 400 Watt ATX12V Power supply
- ATX Motherboards (up to 12 in. x 13 in.)
- External Drive Bays: Three 5.25 in and Three 3.5 in.
- Internal Drive Bays: Seven 3.5 in.
- 7 expansion slots
- 120 mm intake fan and two 80 mm exhaust fans
- 2 USB ports
- **Size:** (177 mm x 483 mm x 584 mm) (7 in. x 19 in. x 23 in.) (HxWxD) excluding slide rails
- **Weight:** Approximately 25.5 kg (56 lbs.)

### Primary Power

- Single or Dual Power Supplies
- Typical 300 Watt, 115 Volts or 230 Volts AC single phase 47-63 Hz
- 14 Amp @ 3.3 V, 30 Amp @ +5 V, 10 Amp @ +12 V Maximum
- UPS option available for increased reliability

### Environmental

- **Operating Temperature:** 0°C to +55°C
- **Storage Temperature:** -40°C to +70°C
- **Operating Humidity:** 20% to 80% (non-condensing)
- **Storage Humidity:** 5% to 90% (non-condensing)

For additional information on specific configurations and pricing, please contact Willowglen Systems Inc.  
VISTA and PAC are trademarks of Willowglen Systems Inc. Specifications subject to change without notice.  
November 2009 Printed in Canada



WILLOWGLEN SYSTEMS INC.  
8522 DAVIES ROAD  
EDMONTON, ALBERTA  
CANADA, T6E 4Y5

Tel: +1 (780) 465-1530  
Fax: +1 (780) 465-0130  
email: [marketing@willowglen.ca](mailto:marketing@willowglen.ca)  
Website: [www.willowglen.ca](http://www.willowglen.ca)